

# VILA®



Self-Priming Pumps and Shallow well Pumps

**VILA®**

Plot No. B 63, Kagal  
Hatkanangale, Five Star MIDC,  
Karveer, Kolhapur,  
Maharashtra - 416 216



salesho@vila.co.in  
Customer Care : 0230 - 2991134  
www.laxmipumpsgroup.com  
www.vila.co.in  
www.laxmioilengines.com





**ViLA Self-Priming Pumps and Shallow well Pumps** are specifically designed and developed with superior manufacturing techniques adhering strictly to the quality standards resulting to a trouble free and reliable operation with minimum maintenance cost.

**Applications :** Residential, Bungalows, Flats, Booster application, Construction, Industrial Usage, Lawns, Gardening, Garages, Laundries, Hotels, Clubs, HVAC Plants.

### VSP Series - Self Priming Pumps

#### Technical Specifications:

**Power** : 0.37 Kw / 0.5 HP to 0.75Kw / 1.0 HP  
**Head** : 4 to 44 Meters  
**Discharge** : 2970 to 430 LPH  
**Speed** : 2880 RPM  
**Type of Duty** : S1 (Continuous)

#### Features:

Sleek Aluminium Body  
 Self-Priming capacity up to 6 Mtrs  
 Fitted with TOP (Thermal overload Protector)  
 SS Shaft with Pr. Die casted Rotors  
 Wide Voltage Design – 160 to 240V

### ViLA Self Priming Pumps

ViLA MODELS	KW	HP	PIPE SIZE	HEAD IN METERS	4	6	10	14	20	24	26	30	32	34	36	38	40	44
VSP 0.5 SD	0.37	0.5	25 X 25	DISCHARGE IN LPH	1900	1800	1580	1300	1000	720								
VSP 0.5 HD	0.37	0.5	25 X 25		1960	1860	1650	1350	1060	780								
VSP 0.5 PRIME	0.37	0.5	25 X 25			2050	1750	1500	1200	950	850							
VSP 1.0 SD	0.75	1.0	25 X 25				2450	2000	1500	1100	900	500						
VSP 1.0 HD	0.75	1.0	25 X 25		2770	2700	2450	2050	1730	1450	1140	820	710	590	470			
VSP 1.0 PRIME	0.75	1.0	25 X 25		2970	2800	2540	2310	2050	1860	1600	1440	1310	1210	950	750	610	430

### VSWJ Series – Shallow well Jet Pumps

#### Technical Specifications:

**Power** : 0.37 Kw / 0.5 HP to 1.1 Kw / 1.5 HP  
**Head** : 6 to 42 Meters  
**Discharge** : 3300 to 300 LPH  
**Speed** : 2880 RPM  
**Type of Duty** : S1 (Continuous)

#### Features:

Sleek Aluminium Body  
 Self-Priming capacity up to 8.5Mtrs  
 Fitted with TOP (Thermal overload Protector)  
 SS Shaft with Pr. Die casted Rotors  
 Wide Voltage Design – 160 to 240V

### ViLA Shallow well Pumps

ViLA MODELS	KW	HP	PIPE SIZE	HEAD IN METERS	6	9	12	15	18	21	24	27	30	33	36	42
V SWJ 0.5	0.37	0.5	25 X 25	DISCHARGE IN LPH	3000	2760	2400	1860	1380	900	600					
V SWJ 1.0	0.75	1.0	25 X 25				3300	3180	3000	2580	2160	1680	1260	780	300	0
V SWJ 1.5	1.1	1.5	25 X 25									2400	2100	1680	1440	720

Note : Due to continuous product developments, the data mentioned in the catalogue may change without any prior notice.

A Brand of



A LAXMI PUMPS GROUP COMPANY

Authorised Distributor / Dealer: